



TECHNICAL DATA SHEET

BIOPET ANTI ALGAE

DESCRIPTION

Special product biocide and anti-algae with a high concentration specifically indicated in cases of contamination of algae and bacteria's in the fuel tanks (especially where used an mixture diesel-biodiesel).It Protects fuel system components against organic acids created by microbial growth and prevents fuel tank corrosion. Prevents fuel-filter plugging, improves fuel performance and reduces engine maintenance costs

APPLICATIONS

Recommended for use continually to prevent the growth of bacteria that can contaminate diesel fuel and cause blockages to fuel filters and lines.

BENEFITS

- ✓ Protects fuel system components against organic acids
- ✓ Prevents fuel-filter plugging
- ✓ Reduces maintenance cost

TECHNICAL DATA

Appearance :	Liquid
Vapor pressure :	10 kPa at 20°C
Explosive limits :	
<i>Lower Explosion Limit</i>	LEL 0,6 % vol
<i>Upper Explosion Limit</i>	UEL 7 % vol
Flash point :	23,5 °C at 1,013 hPa
Initial boiling point :	97°C at 1,013 hPa
Auto-ignition temperature :	> 200°C

USE DIRECTION

- Normal Use (preventive treatment) 1 L to 6000 L fuels
- Bacterial Growth (curative treatment) 10 L to 6000 L fuels

The above mentioned typical data are approximate values based on current production and can be subject of allowable production tolerances

For further assistance on the product please contact customer service or technical department